





INTRODUCING THE

# RED ELEPHANT LOCK



SIMPLY THE TOUGHEST






# SPECIFICATIONS

TYPE	CROSS KIT 	TRILOBE 		540 RPM				1000 RPM			
		INNER	OUTER	kW	HP	N-m	in-lbs	kW	HP	N-m	in-lbs
AB1	22.0 x 54.0	26.6	32.4	12	16	210	1850	18	25	72	1500
AB2	23.8 x 61.3	29.0	36.1	15	21	270	2400	23	31	220	1950
AB3	27.0 x 70.0	36.1	43.4	26	35	460	4050	40	55	380	3350
AB4	27.0 x 74.6	36.1	43.4	26	35	460	4050	40	55	380	3350
AB5	30.2 x 79.4	44.7	51.3	35	47	620	5500	54	74	520	4600
AB6	30.2 x 91.4	44.7	53.6	47	64	830	7350	74	100	710	6250
AB7	30.2 x 106.5	44.7	53.6	55	75	970	8600	87	118	830	7350
AB7N	35.0 x 93.5	44.7	53.6	55	75	970	8600	87	118	830	7350
AB8	35.0 x 106.0	53.6	62.7	70	95	1240	10950	110	150	1050	9300
AB9	41.0 x 108.0	53.6	62.7	88	118	1560	13750	134	180	1280	11325









TYPE	CROSS KIT 	SQUARE 		540 RPM				1000 RPM			
		INNER	OUTER	kW	HP	N-m	in-lbs	kW	HP	N-m	in-lbs
RPM-6R	31/32x2 9/32	3/4x7/8	1x1 1/8	12	16	210	1850	22	30	210	1890
RPM-12R	1 1/16x2 1/2	1x1 1/8	1 1/4x1 3/8	19	26	340	3030	33	44	310	2770
RPM-14R	1 1/8x2 5/8	1x1 1/8	1 1/4x1 3/8	28	37	490	4320	42	56	400	3530
RPM-35R	1 1/4x3 13/64	1 3/16x1 3/16	2 1/8 round	48	65	860	7590	75	100	710	6300
RPM-44R	1 5/16x4	1 3/16x1 3/16	2 1/8 round	67	90	1190	10500	101	135	960	8510
RPM-55R	1 17/32x4 19/64	1 3/16x1 3/16	2 1/8 round	95	127	1670	14820	146	196	1400	12350









TYPE	CROSS KIT 	LEMON 		540 RPM				1000 RPM			
		INNER	OUTER	kW	HP	N-m	in-lbs	kW	HP	N-m	in-lbs
RPM-L1	22.0 x 54.0	23.7	30.0	12	16	210	1850	18	24	175	1550
AW10	22.0 x 54.6	23.7	30.0	11	15	190	1690	17	23	160	1440
AW10S	22.0 x 54.6	34.5	41.2	12	16	210	1850	18	24	170	1500
AW20S	23.8 x 61.3	23.7	30.0	13	17	230	2030	20	27	190	1690
AW20	23.8 x 61.3	34.5	41.2	20	27	355	3140	31	42	295	2610
RPM-L3	27.0 x 70.0	34.5	41.2	24	32	400	3530	37	50	320	2830
AW21	27.0 x 74.6	34.5	41.2	28	37	500	4420	44	59	415	3670
RPM-L5	30.2 x 80.0	39.5	48.0	35	47	620	5500	51	68	500	4420
RPM-L6	30.2 x 92.0	39.5	48.0	40	54	850	7500	61	82	690	6100
AW21S	27.0 x 74.6	39.5	48.0	28	37	500	4420	43	58	410	3630
AW35	32.0 x 76.0	39.5	48.0	38	51	670	5950	58	78	550	4900









TYPE	CROSS KIT 	STAR 		540 RPM				1000 RPM			
		INNER	OUTER	kW	HP	N-m	in-lbs	kW	HP	N-m	in-lbs
RPM-H6	30.2 x 92.0	51.4	60.8	40	54	850	7500	61	82	690	6100
RPM-H7	30.2 x 106.5	51.4	60.8	55	74	1000	8850	78	105	810	7150
AW35S	32.0 x 76.0	51.4	60.8	41	55	730	6420	63	84	600	5320
RPM-HN7	35.0 x 94.0	51.4	60.8	51	68	970	8600	87	117	830	7350
RPM-H8	35.0 x 106.5	51.4	60.8	66	89	1250	11060	100	134	1020	9030
AW36	36.0 x 89.0	51.4	60.8	66	89	1175	10400	102	137	975	8630
AW26S	42.0 x 104.0	51.4	60.8	51	68	900	7980	78	105	740	6590
AW26	42.8 x 104.0	61.4	71.5	79	106	1400	12350	125	168	1190	10500



SAFETY SHIELD	SHEAR BOLT CLUTCH	OVERRUNNING CLUTCH	RADIAL PIN CLUTCH	FRICITION CLUTCH	FRICITION CLUTCH w/ OVERRUNNING CLUTCH	COVERED FRICITION CLUTCH	WIDE ANGLE JOINT
							
R12108							
R12108	•	•	•	•	•		
R12108							
R12108							
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•		•
R12109	•	•	•	•	•		
R12109	•	•	•	•	•		
R12109	•	•	•	•	•		
R12109	•	•	•	•	•		
R12109	•	•	•	•	•		

SAFETY SHIELD	SHEAR BOLT CLUTCH	OVERRUNNING CLUTCH	RADIAL PIN CLUTCH	FRICITION CLUTCH	FRICITION CLUTCH w/ OVERRUNNING CLUTCH	COVERED FRICITION CLUTCH	WIDE ANGLE JOINT
							
R12108							
R12108	•	•	•	•	•	•	•
R12108	•	•	•	•	•	•	•
R12108	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•

SAFETY SHIELD	SHEAR BOLT CLUTCH	OVERRUNNING CLUTCH	RADIAL PIN CLUTCH	FRICITION CLUTCH	FRICITION CLUTCH w/ OVERRUNNING CLUTCH	COVERED FRICITION CLUTCH	WIDE ANGLE JOINT
							
R12108							
R12108	•	•	•	•	•	•	•
R12108	•	•	•	•	•	•	•
R12108	•	•	•	•	•	•	•
R12108	•	•	•	•	•	•	•
R12108	•	•	•	•	•	•	•
R12108	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•

SAFETY SHIELD	SHEAR BOLT CLUTCH	OVERRUNNING CLUTCH	RADIAL PIN CLUTCH	FRICITION CLUTCH	FRICITION CLUTCH w/ OVERRUNNING CLUTCH	COVERED FRICITION CLUTCH	WIDE ANGLE JOINT
							
R12109							
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•
R12109	•	•	•	•	•	•	•

\*AVAILABLE UNDER SPECIAL ORDER



# SHIFTING THE BALANCE OF POWER

INNOVATORS AND GLOBAL MANUFACTURERS OF POWERTRAIN SOLUTIONS

**OMNI Powertrain Solutions** has created the most compact, powerful, light-weight axial flux electric motor powertrain systems on earth. Innovation is our core value, and whether we are manufacturing mechanical drivelines for agricultural equipment, hydrostatic powertrain systems for off-highway equipment or state-of-the-art electric powertrain systems for commercial vehicles and motorsports, we strive to exceed the power and quality demanded by our clients no matter their industry.

REGGIO EMILIA  
I T A L Y

SHANGHAI  
C H I N A

HOUSTON  
T E X A S

Our diverse family of manufacturing firms ensure that **OMNI** always provides unparalleled service, distribution and support. From conception through development we have a single objective: to provide the highest performance electric, hydrostatic and mechanical powertrain systems that meet the objectives of our clients.

# OMNI

POWERTRAIN TECHNOLOGIES

## AMERICA

3620 West 11th Street  
Houston, Texas 77008

**Tel** +1 713 635 6331  
**Fax** +1 713 635 6360

## ASIA

2455 Bao'an Highway  
Jiading Malu, Shanghai 201801

**Tel** +86 21 69153123  
**Fax** +86 21 69154218

## EUROPE

Via Giovanni, Rinaldi 105  
Reggio Emilia, Italy 42124

**Tel** +39 051 758517  
**Fax** +39 051 751575

W W W . O M N I P O W E R T R A I N . C O M

THE FOLLOWING PRODUCT LINES ARE PART OF THE **OMNI POWERTRAIN FAMILY**

